



ROLLER SHUTTER AND LIGHT BOTTOM BAR SECURITY LOCKS GENERAL SPECIFICATION

PRODUCT RANGE

IRON OR ALUMINIUM LOCKERS:

- Central or side application.
- Round cylinder: from outside/inside by same symmetric key.
- Double bit key system: from outside/inside operation by same symmetric key.
- Knob: from inside only with stop safety device.
- Unassembled or assembled spurs on bolts.
- Bent bolts for central or side application.
- Flat bolts for central application.
- Oversize bent bolt projection.
- Paired right and left keyed alike.
- Accessories available.
- Locks can be supplied keyed alike (KA)
- Suitable for replacing same kinds of locks.

SECURITY FEATURES

- Large range of key combinations.

MATERIAL SPECIFICATION

- Steel case and bolts.
- Extruded solid brass cylinder body and plug.
- Inox steel cylinder springs.
- Brass strip for keys.

FINISHES

- Zinc plated case and bolts.

PACKING

- Singly or multi boxed.

GUARANTEE

- All our locks are covered by a 5 year mechanical guarantee.



ROLLER SHUTTER LOCKS

GENERAL SPECIFICATION

Single throw. Gear mechanism.
 25 mm. Ø round cylinder. 7 mm. cylinder projection.
 Opening by same key from both sides.

45 mm. bolt projection as standard. 23 mm. throw.
Zinc plated.
 3 nickel plated brass keys.

| COD. | | € |
|------------|--------------------------------|----------------------------------|
| | CENTRAL TYPE | |
| | F 10 01 00 | Flat bolts. Unassembled spurs. 1 |
| | F 10 01 10 | Flat bolts. Assembled spurs. 1 |
| | F 10 00 00 | Bent bolts. Unassembled spurs. 1 |
| F 10 00 10 | Bent bolts. Assembled spurs. 1 | |

| COD. | | € |
|------------|---|------------------------------------|
| | SIDE TYPE | |
| | F 11 00 00 | Right. Bent bolt. Without spurs. 1 |
| | F 12 00 00 | Left. Bent bolt. Without spurs. 1 |
| | PAIR OF SIDE TYPE LOCKS RIGHT ANF LEFT KEYED ALIKE | |
| F 11 22 00 | Bent bolts. Without spurs. 1 | |

SPECIAL FEATURES ON REQUEST

| COD. | | € |
|-------------|---|----------------------------------|
| | Oversize bent bolt projection without spurs. | |
| | F 11 00 3_ | Right. 70 mm. bolt projection. 1 |
| | F 11 00 5_ | Right. 90 mm. bolt projection. 1 |
| | F 12 00 3_ | Left. 70 mm. bolt projection. 1 |
| | F 12 00 5_ | Left. 90 mm. bolt projection. 1 |
| | F 11 22 3_ | Pair. 70 mm. bolt projection. 1 |
| | F 11 22 5_ | Pair. 90 mm. bolt projection. 1 |
| | Overcharge for no. 2 fixing plates assembled on the locks. | |
| | F 10 0_ _1 | Central. Fixed by screws. 1 |
| | F 11 00_ _1 | Right. Fixed by screws. 1 |
| F 12 00_ _1 | Left. Fixed by screws. 1 | |
| F 11 22_ _1 | Pair. Fixed by screws. 1 | |

ACCESSORIES FOR ROLLER SHUTTER LOCKS

| COD. | | € |
|------|------------------|--|
| | F 60 054 00 28 1 | no. 2 fixing plates with screws. 50 Suitable for F 10 - F 11 - F 12 models. |

SHUTTER LOCKS DOUBLE BIT KEY SYSTEM WITH 6 GORGES



GENERAL SPECIFICATION

Double throw.
25 mm. Ø round cylinder. 5,5 mm. cylinder projection.
Opening by same key from both sides.

46 mm. bolt projection as standard. 22 mm. throw.
Zinc plated.
2 nickel plated brass keys.

| | COD. | | € |
|--|---|--------------------------------------|---|
| | CENTRAL TYPE | | |
| | F 30 00 00 | Flat bolts. Unassembled spurs. | 6 |
| | SIDE TYPE | | |
| | F 31 00 00 | Right. Flat bolts. Without spurs. | 6 |
| | F 32 00 00 | Left. Flat bolts. Without spurs. | 6 |
| | PAIR OF SIDE TYPE LOCKS RIGHT AND LEFT KEYED ALIKE | | |
| | F 31 22 00 | Flat bolts. Without spurs. | 3 |



LIGHT BOTTOM BAR AND METAL CABINET LOCKS

GENERAL SPECIFICATION

Opening by same key from both sides.
Single throw. Gear mechanism.
23 mm. Ø round cylinder. 12 mm. cylinder projection.

28,2 mm. throw.
Zinc plated.
2 nickel plated brass keys

| COD. | | € |
|------|---------------------|-----------------------------------|
| | CENTRAL TYPE | |
| | F 20 00 00 | Flat bolts. Unassembled spurs. 50 |
| | F 20 00 10 | Flat bolts. Assembled spurs. 50 |

Opening from inside only by knob.
Special spring stopping device securing closed or open position.

28,2 mm. throw.
Zinc plated.

| COD. | | € |
|------|---------------------|-----------------------------------|
| | CENTRAL TYPE | |
| | F 23 00 00 | Flat bolts. Unassembled spurs. 50 |
| | F 23 00 10 | Flat bolts. Assembled spurs. 50 |